

HYCON HH25 BREAKER

ANTI-VIBRATION HANDLES

WORKS REGARDLESS OF DUST AND WATER



PRODUCT FEATURES

HYCON HH25 is compact and delivers very high performance in relation to its weight. It is designed for tough jobs of breaking reinforced concrete, asphalt, frozen ground, etc.

The HYCON vibration-reduced handle is standard with the HH25, available in 20 and 30-lpm types.

It is mainly used by contractors, armies, asphalt companies, supply companies, rentals, etc. The standard tool size is hex 32 x 160 mm.

The breaker can connect the HPP series and other hydraulic power sources. Different tool sizes are available on request.

HYDRAULIC BREAKER HH25

	CE	CE	CE	CE
	30LPM 28x160	20LPM 32x160	30LPM 32x160	20LPM 32x152
Item no.	1010906	1010025	1010125	1010225
Weight [kg / lbs]	25.3 / 55.8	25.8 / 56.9	25.8 / 56.9	25.8 / 56.9
Oil flow [LPM / GPM]	30 / 8	20 / 5	30 / 8	20 / 5
Working pressure [bar / psi]	120 / 1740	120 / 1740	120 / 1740	120 / 1740
Max pressure [bar / psi]	160 / 2320	160 / 2320	160 / 2320	160 / 2320
Tool shank HEX [mm] (optional)	28 x 160	32 x 160	32 x 160	32 x 152
Blow frequency [Hz]	1380	1380	1380	1380
Blow energy [joule]	95	85	95	85
Sound power level L _{Wa} [dB]	108	108	108	108
Vibration level, 3 axis [m/s ²]	9.4	9.4	9.4	9.4

ACCESSORIES

Dust suppression kit, item no. 3030051. HYCON water container item no. 1113286.

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS · CORE DRILLS · POST DRIVERS · PICK HAMMER · LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS · ROCK DRILLS · UNDERWATER EQUIPMENT · GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel.: +45 9647 5200
Mail: hycon@hycon.dk
www.hycon.dk

DISTRIBUTOR: